



SAFETY DATA SHEET

MAALARIN VALKOLAKKA 30

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : MAALARIN VALKOLAKKA 30
Product description : Alkyd paint.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Painting work

1.3 Details of the supplier of the safety data sheet

Manufacturer or Distributor

Tikkurila Oyj
P.O. Box 53
FI-01301 VANTAA
FINLAND
Telephone +358 20 191 2000

e-mail address of person responsible for this SDS : Tikkurila Oyj,
Product Safety,
e-mail: productsafety@tikkurila.com

1.4 Emergency telephone number

Telephone number : 112
(24h)

Supplier or Manufacturer

Telephone number : Tikkurila Oyj
+358 20 191 2000 (GMT +2) Mon-Fri 8-16

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]
Flam. Liq. 3, H226

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

2.2 Label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 - Flammable liquid and vapor.

Precautionary statements

General : P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.

Prevention : P210 - Keep away from sparks and open flames. - No smoking.
P261 - Avoid breathing vapor.
P271 - Use only outdoors or in a well-ventilated area.

Response	: Not applicable.
Storage	: Not applicable.
Disposal	: Not applicable.
Supplemental label elements	: Contains cobalt bis(2-ethylhexanoate) and ethyl methyl ketoxime. May produce an allergic reaction. Wear protective gloves.

2.3 Other hazards

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification Regulation (EC) No. 1272/2008 [CLP]	Notes
hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	REACH #: 01-2119463258-33 EC: 919-857-5 CAS: -	≥10 - <20	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 EUH066	H,P
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	REACH #: 01-2119457273-39 EC: 918-481-9	≤3	Asp. Tox. 1, H304 EUH066	-
2-ethylhexanoic acid, zirconium salt	REACH #: 01-2119979088-21 EC: 245-018-1 CAS: 22464-99-9	≤1	Repr. 2, H361d (Unborn child)	-
ethyl methyl ketoxime	REACH #: 01-2119539477-28 EC: 202-496-6 CAS: 96-29-7 Index: 616-014-00-0	≤0.3	Acute Tox. 4, H312 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351	-
cobalt bis(2-ethylhexanoate)	REACH #: 01-2119524678-29 EC: 205-250-6 CAS: 136-52-7	<0.25	Eye Irrit. 2, H319 Skin Sens. 1, H317 Repr. 2, H361f (Fertility) Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1) See Section 16 for the full text of the H statements declared above.	-

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Notes, if applicable, refer to Notes given in Annex VI of 1272/2008/EC.

SECTION 4: First aid measures

4.1 Description of first aid measures

General	: In all cases of doubt, or when symptoms persist, seek medical attention. Show this safety data sheet or label to the doctor if possible.
Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with plenty of lukewarm water, keeping eyelids open. Continue to rinse for at least 15 minutes. Get medical attention if symptoms occur.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion : If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Remove to fresh air and keep at rest in a position comfortable for breathing. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Inhalation of vapours may cause dizziness, headache and nausea.
See Section 11 for more detailed information on health effects and symptoms.

Contains:

cobalt bis(2-ethylhexanoate)

ethyl methyl ketoxime

May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire. Recommended: Alcohol resistant foam, CO₂, powders or water spray/mist.

Unsuitable extinguishing media : Do not use a direct water jet that could spread the fire.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Flammable liquid and vapor. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Hazardous combustion products : When exposed to high temperatures, hazardous decomposition products may be produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

5.3 Advice for firefighters

Special protective actions for fire-fighters : Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. Do not release runoff from fire to drains or watercourses.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures : Shut off all ignition sources. No flares, smoking or flames in hazard area. Provide adequate ventilation. Avoid breathing vapor or mist. Avoid direct skin contact with product. See Section 8 for information on appropriate personal protective equipment.

6.2 Environmental precautions : Do not allow to enter drains, water courses or soil.

6.3 Methods and materials for containment and cleaning up : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

: Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. Isolate from sources of heat, sparks and open flame. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. No sparking tools should be used.

Avoid contact with skin and eyes. Avoid breathing vapor. Avoid inhalation of dust from sanding. Wear appropriate respirator when ventilation is inadequate. See Section 8 for information on appropriate personal protective equipment. Eating, drinking and smoking should be prohibited in areas where this material is handled and stored. Wash hands before breaks and immediately after handling the product.

Risk of self-ignition! Materials such as cleaning rags and paper wipes, sanding dust and overspray containing the product, may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be placed in a metal container filled with water and sealed or dried preferably outdoors or incinerated immediately. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

7.2 Conditions for safe storage, including any incompatibilities

: Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store and use away from heat, sparks, open flame or any other ignition source. No smoking. Keep container tightly closed. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Recommended storage temperature is +5°C ...+25°C. Store in accordance with local regulations.

7.3 Specific end use(s)

: None.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. Use explosion-proof ventilation equipment. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn (see Personal protection). Comply with the health and safety at work laws.

Individual protection measures

Eye/face protection : Use safety eyewear designed to protect against splash of liquids (EN166).

- Hand protection** : Wear protective gloves. Gloves should be replaced regularly and if there is any sign of damage to the glove material. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.
Recommended glove material (EN374):
> 8 hours (breakthrough time): nitrile rubber, laminated foil
- Skin protection** : Wear suitable protective clothing. This product is classified as flammable. If necessary, personnel should wear antistatic clothing made of natural fibers or of high-temperature-resistant synthetic fibers.
- Respiratory protection** : If ventilation is inadequate, use respirator that will protect against organic vapor and dust/mist. Wear a half mask or full face respirator with gas and vapor filter A and dust filter P2 during sanding (EN140:1998, EN405:2001). During continuous and long-term work the use of motor-driven or air-fed respirators is recommended (EN12941:1998). Be sure to use an approved/certified respirator or equivalent. Check that mask fits tightly and change filter regularly.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Various
- Odor** : Strong.
- Odor threshold** : Not relevant for the hazard assessment of the product.
- pH** : Not relevant for the hazard assessment of the product.
- Melting point/freezing point** : <-15°C (hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)
- Initial boiling point and boiling range** : 150 to 200°C (hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)
- Flash point** : 36 °C (hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)
- Evaporation rate** : Not relevant due to the nature of the product.
- Flammability (solid, gas)** : Not applicable. Product is a liquid.
- Upper/lower flammability or explosive limits** : Lower: 0.6% (hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)
Upper: 7% (hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)
- Vapor pressure** : 0.3 kPa [room temperature] (hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)
- Vapor density** : >3 (hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)
- Density** : 0.73 g/cm³
- Solubility(ies)** : insoluble in water.
- Partition coefficient: n-octanol/ water** : Not available.
- Auto-ignition temperature** : 250°C (hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)
- Decomposition temperature** : Not relevant for the hazard assessment of the product.
- Viscosity** : Kinematic (40°C): >20.5 mm²/s
>60 s [ISO 6mm cup]
- Explosive properties** : No explosive ingredients present.
- Oxidizing properties** : No oxidizing ingredients present.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

- 10.1 Reactivity** : See Section 10.5.
- 10.2 Chemical stability** : Stable under recommended storage and handling conditions (see Section 7).
- 10.3 Possibility of hazardous reactions** : May present an explosion hazard when material is suspended in air in confined areas or equipment and subjected to spark, heat or flame.
- 10.4 Conditions to avoid** : Avoid extreme heat and freezing. Avoid all possible sources of ignition (spark or flame).
- 10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions:
oxidizing agents
strong acids
strong alkalis
- 10.6 Hazardous decomposition products** : When exposed to high temperatures, hazardous decomposition products may be produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There is no testdata available on the product itself.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting.

Acute toxicity

Not classified.

Irritation/Corrosion

Not classified.

Sensitization

Contains small amounts of sensitizing substances:

cobalt bis(2-ethylhexanoate)

ethyl methyl ketoxime

Mutagenicity

Not classified.

Carcinogenicity

Not classified.

Reproductive toxicity

Not classified.

Teratogenicity

Not classified.

Specific target organ toxicity (single exposure)

Not classified.

Specific target organ toxicity (repeated exposure)

Not classified.

Aspiration hazard

Not classified.

SECTION 12: Ecological information

Ecological testing has not been conducted on this product.
Do not allow to enter drains, water courses or soil.

The product is not classified as environmentally hazardous according to Regulation (EC) 1272/2008.

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
cobalt bis(2-ethylhexanoate)	IC50 0.528 mg/l	Algae	72 hours

12.2 Persistence and degradability : No specific data.

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	Bioconcentration factor [BCF]	Potential
cobalt bis(2-ethylhexanoate)	-	15600	high
ethyl methyl ketoxime	0.63	2.5 to 5.8	low
2-ethylhexanoic acid, zirconium salt	-	2.96	low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

vPvB : Not applicable.

12.6 Other adverse effects : Not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : Remove as much product as possible from the tools before cleaning. Liquid residue and cleaning liquids are hazardous waste and must not be emptied into drains or sewage system, but handled in accordance with national regulations. Product residues should be left at special companies which have permission for gathering this kind of wastes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

Packaging

Methods of disposal : Empty packaging should be recycled or disposed of in accordance with national regulations.

Special precautions : **Risk of self-ignition!** Materials such as cleaning rags and paper wipes, sanding dust and overspray containing the product, may spontaneously self-ignite some hours later. To avoid the risks of fires, waste like this should be placed in a metal container filled with water and sealed before disposal, or dried preferably outdoors or incinerated immediately.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3
14.4 Packing group	III	III	III
14.5 Environmental hazards	No.	No.	No.

Additional information

ADR/RID : **Viscous substance exemption** This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.
Tunnel code (D/E)

IMDG : **Emergency schedules** F-E,S-E
Viscous substance exemption This class 3 viscous liquid is not subject to regulation in packagings up to 30 L according to 2.3.2.5.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Other EU regulations

Europe inventory : Not determined.

Product/ingredient name	Carcinogenic effects	Mutagenic effects	Developmental effects	Fertility effects
2-ethylhexanoic acid, zirconium salt	-	-	Repr. 2, H361d (Unborn child)	-
ethyl methyl ketoxime	Carc. 2, H351	-	-	-
cobalt bis (2-ethylhexanoate)	-	-	-	Repr. 2, H361f (Fertility)

VOC Directive : This product is in scope of Directive 2004/42/CE.

15.2 Chemical Safety Assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EUH statement = CLP-specific Hazard statement
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 RRN = REACH Registration Number
 vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification

Justification

Flam. Liq. 3, H226

On basis of test data

Full text of abbreviated H statements

: H226 Flammable liquid and vapor.
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H351 Suspected of causing cancer.
 H361d Suspected of damaging the unborn child.
 H361f Suspected of damaging fertility.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

: Acute Tox. 4, H312 ACUTE TOXICITY (dermal) - Category 4
 Aquatic Acute 1, H400 AQUATIC HAZARD (ACUTE) - Category 1
 Aquatic Chronic 1, H410 AQUATIC HAZARD (LONG-TERM) - Category 1
 Asp. Tox. 1, H304 ASPIRATION HAZARD - Category 1
 Carc. 2, H351 CARCINOGENICITY - Category 2
 EUH066 Repeated exposure may cause skin dryness or cracking.
 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
 Flam. Liq. 3, H226 FLAMMABLE LIQUIDS - Category 3
 Repr. 2, H361d TOXIC TO REPRODUCTION (Unborn child) - Category 2
 Repr. 2, H361f TOXIC TO REPRODUCTION (Fertility) - Category 2
 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1
 STOT SE 3, H336 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

Date of issue/ Date of revision : 6/6/2018

Date of previous issue : 5/14/2015

Version : 1.01

Notice to reader

This Safety Data Sheet is prepared in accordance with Annex II (EU) No 830/2015 to Regulation (EC) No 1907/2006 (REACH). The information contained in this Safety Data Sheet is based on the present state of knowledge and current EU and national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.