Conforms to Regulation	(EC) No. 1907/2006 (REA	CH), Annex II, as amended by Commissio	on Regulation (EU)
2020/878 - Europe			
Date of issue/ Date of	11/23/2022	Date of previous issue	: 4/4/2022

TIKKURILA

revision

SAFETY DATA SHEET

ACOUSTICS

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Product name

: ACOUSTICS

Product description : A one-component water-borne noise damping coating.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Painting work

1.3 Details of the supplier of the safety data sheet

 Manufacturer or Distributor

 Tikkurila Oyj

 P.O. Box 53

 FI-01301 VANTAA

 FINLAND

 Telephone +358 20 191 2000

 e-mail address of person

 responsible for this SDS

 Product Safety,

 e-mail: productsafety@tikkurila.com

1.4 Emergency telephone number

Telephone number	:	112
-		(24h)

Supplier or Manufacturer

Telephone number: Tikkurila Oyj+358 20 191 2000 (GMT +2) Mon-Fri 8-16

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

2.2 Label elements

Hazard pictograms

	\land
<	!>

: Not applicable.

Signal word	:	Warning
Hazard statements	:	■317 - May cause an allergic skin reaction. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements		

2

Version : 4

General

Date of issue/Date of revision	23.11.2022 Date of previous issue 04.04.2022. ACOUSTICS
Prevention	 P261 - Avoid breathing mist/spray. P280 - Wear protective gloves. P284 - In case of inadequate ventilation wear respiratory protection. P273 - Avoid release to the environment.
Response	: P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.
Storage	: Not applicable.
Disposal	: Not applicable.
Hazardous ingredients	: 2-octyl-2H-isothiazol-3-one (OIT)
Supplemental label elements	 Contains small amounts of sensitizing substances: 1,2-benzisothiazol-3(2H)-one (BIT), reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H- isothiazol-3-one (3:1) (C(M)IT/MIT (3:1)).

Treated articles

This product contains a biocidal product for the preservation of the product during storage. Contains BIT, C(M)IT/MIT (3:1).

2.3 Other hazards

Other hazards which do : None known. not result in classification

SECTION 3: Composition/information on ingredients

			Classification		
Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Notes	
34odo-2-propynyl butylcarbamate (IPBC)	REACH #: 01-2120762115-60 EC: 259-627-5 CAS: 55406-53-6	<0.1	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)	-	
I,2-benzisothiazol-3(2H)-one (BIT)	EC: 220-120-9 CAS: 2634-33-5	<0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411	-	
2-octyl-2H-isothiazol-3-one (OIT)	EC: 247-761-7 CAS: 26530-20-1 Index: 613-112-00-5	<0.025	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071	-	
reaction mass of 5-chloro-2-methyl- 2H-isothiazol-3-one and 2-methyl- 2H-isothiazol-3-one (3:1) (C(M)IT/ MIT (3:1))	CAS: 55965-84-9 Index: 613-167-00-5	<0.001	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071 See Section 16 for the full	-	
			text of the H statements declared above.		

Notes, if applicable, refer to Notes given in Annex VI of 1272/2008/EC. **Specific concentration limits and ATE-values**

Date of issue/Date of revision

23.11.2022 Date of previous issue

ACOUSTICS

04.04.2022.

Ingredient name, Specific concentration limits, ATE value

√2-benzisothiazol-3(2H)-one (BIT) Skin Sens. 1, H317: C ≥ 0,05 %

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1)) Skin Corr. 1C, H314: $C \ge 0,6 \%$ Skin Irrit. 2, H315: 0,06 % $\le C < 0,6 \%$ Eye Dam. 1, H318: $C \ge 0,6 \%$ Eye Irrit. 2, H319: 0,06 % $\le C < 0,6 \%$ Skin Sens. 1A, H317: $C \ge 0,0015 \%$

2-octyl-2H-isothiazol-3-one (OIT) Skin Sens. 1A, H317: C \ge 0,0015 % Inhalation: ATE = 0.27 mg/L (dusts/mists) Dermal: ATE = 311 mg/kg bw Oral: ATE = 125 mg/kg bw

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

: In all cases of doubt, or when symptoms persist, seek medical attention. Show this safety data sheet or label to the doctor if possible.
: Check for and remove any contact lenses. Immediately flush eyes with plenty of lukewarm water, keeping eyelids open. Continue to rinse for at least 15 minutes. Get medical attention if symptoms occur.
: Remove to fresh air. Keep person warm and at rest.
: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. Get medical attention if symptoms occur.
: If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Remove to fresh air and keep at rest in a position comfortable for breathing. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction. See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures 5.1 Extinguishing media

Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire. Recommended: Alcohol resistant foam, CO ₂ , powders or water spray/mist.	
Unsuitable extinguishing media	: Do not use a direct water jet that could spread the fire.	

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	: This product is not classified as flammable. Fire will produce dense black sn Exposure to decomposition products may cause a health hazard.	10ke.
Hazardous combustion products	: When exposed to high temperatures, hazardous decomposition products ma produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen	

04.04.2022.

5.3 Advice for firefighters Special protective actions for fire-fighters	: Use water spray to keep fire-exposed containers cool. This material is hazardous to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
SECTION 6: Acciden	tal release measures
6.1 Personal precautions.	: Provide adequate ventilation. Avoid breathing vapor or mist. Avoid direct skin

emergency procedures	contact with product. See Section 8 for information on appropriate personal protective equipment.
6.2 Environmental precautions	: Hazardous to aquatic environment. Do not allow to enter drains, water courses or soil.
6.3 Methods and materials for containment and cleaning up	: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Preferably clean with water or detergent. Avoid using solvents.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling	:	Skin contact with the product and exposure to spray mist and vapor should be avoided. Avoid contact with skin and eyes. Avoid inhalation of dust from sanding. See Section 8 for information on appropriate personal protective equipment. Eating, drinking and smoking should be prohibited in areas where this material is handled and stored. Wash hands before breaks and immediately after handling the product. Avoid release to the environment.
7.2 Conditions for safe storage, including any incompatibilities	:	Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep container tightly closed. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Recommended storage temperature is +5°C+25°C. Do not allow to freeze. Store in accordance with local regulations.
7.3 Specific end use(s)	:	None.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits No exposure limit value known.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls

Date of issue/Date of revision	23.11.2022 Date of previous issue	04.04.2022.	ACOUSTICS

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn (see Personal protection). Comply with the health and safety at work laws.

Individual protection measures

Eye/face protection	: Use safety eyewear (EN166), especially during spray-application.
Hand protection	 Always wear approved protective gloves against chemicals. Gloves should be replaced regularly and if there is any sign of damage to the glove material. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Recommended glove material (EN374): > 8 hours (breakthrough time): nitrile rubber Not recommended: PVA gloves
Skin protection	: Wear suitable protective clothing.
Respiratory protection	: If ventilation during spray-application is inadequate, use respirators with combination filter AP, gas/dust filter (EN405:2001). Wear a half mask or full face respirator with gas and vapor filter A and dust filter P2 during sanding (EN140:1998, EN405:2001). During continuous and long-term work the use of motor-driven or airfed respirators is recommended (EN12941:1998). Be sure to use an approved/ certified respirator or equivalent. Check that mask fits tightly and change filter regularly.
Environmental exposure controls	For information regarding environmental protection measures, please refer to section 13 for waste handling, section 7 for handling and storage and section 1.2 for relevant identified uses of the substance or mixture and uses advised against.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical	l a	nd chemical properties
Appearance		
Physical state	:	Liquid.
Color	:	White.
Odor	:	Mild.
Odor threshold	:	Not relevant for the hazard assessment of the product.
рН	:	🖻 to 9
Melting point/freezing point	:	0°C (water)
Initial boiling point and boiling range	:	100°C (water)
Flash point	:	> 100 °C
Evaporation rate	:	Not relevant due to the nature of the product.
Flammability (solid, gas)	:	Not applicable. Product is a liquid.
Upper/lower flammability or explosive limits	:	No flammable ingredients present.
Vapor pressure	:	3.2 kPa [room temperature] (water)
Vapor density	:	Not relevant for the hazard assessment of the product.
Density	:	1.3 g/cm³
Solubility(ies)	:	Miscible in water.
Partition coefficient: n-octanol/ water	:	Not applicable.
Auto-ignition temperature	:	Not relevant due to the nature of the product.
Decomposition temperature	:	Not relevant for the hazard assessment of the product.
Viscosity	:	Not relevant for the hazard assessment of the product.
Explosive properties	:	No explosive ingredients present.
Oxidizing properties	:	No oxidizing ingredients present.
Particle characteristics		
Median particle size	:	Not applicable.
9.2 Other information		

Version : 4

ACOUSTICS

04.04.2022.

No additional information.

SECTION 10: Stability and reactivity			
10.1 Reactivity	: See Section 10.5.		
10.2 Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).		
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.		
10.4 Conditions to avoid	: Avoid extreme heat and freezing.		
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents strong acids strong alkalis		

10.6 Hazardous	1	When exposed to high temperatures, hazardous decomposition products may be
decomposition products		produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There is no testdata available on the product itself.

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Long term exposure to spray mist may produce respiratory tract irritation. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Acute toxicity

Not classified.

Irritation/Corrosion

Not classified.

Sensitization

May cause an allergic skin reaction.

The product contains sensitizing substances mentioned in sections 2 and 3.

Mutagenicity

Not classified.

Carcinogenicity

Not classified.

Reproductive toxicity

Not classified.

Teratogenicity

Not classified.

Specific target organ toxicity (single exposure)

Not classified.

Specific target organ toxicity (repeated exposure)

Not classified.

Aspiration hazard

Not classified.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not applicable.

11.2.2 Other information

Not available.

04.04.2022.

SECTION 12: Ecological information

Ecological testing has not been conducted on this product. The product is classified as environmetally hazardous according to Regulation (EC) 1272/2008. Harmful to aquatic life with long lasting effects.

Do not allow to enter drains, water courses or soil.

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
riodo-2-propynyl butylcarbamate (IPBC)	EC50 0.053 mg/l	Algae	72 hours
	EC50 0.16 mg/l	Daphnia	48 hours
	LC50 0.067 mg/l	Fish	96 hours
	NOEC 0.05 mg/l	Daphnia - Daphnia magna	21 days
1,2-benzisothiazol-3(2H)- one (BIT)	Acute EC50 0.36 mg/l	Algae - Skeletonema costatum	72 hours
	Acute LC50 0.74 mg/l	Fish	96 hours
2-octyl-2H-isothiazol-3-one (OIT)	Acute EC50 0.00129 mg/l	Algae - Navicula pelliculosa	48 hours
	Acute EC50 0.013 mg/l	Crustaceans - Crassostrea virginica	96 hours
	Acute LC50 0.047 mg/l	Fish - Oncorhynchus mykiss	96 hours
	Chronic EC10 0.000224 mg/l	Algae - Navicula pelliculosa	48 hours
	Chronic NOEC 0.003 mg/l	Daphnia - Daphnia magna	21 days
	Chronic NOEC 0.0085 mg/l	Fish - Pimephales promelas	35 days

12.2 Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Peaction mass of 5-chloro- 2-methyl-2H-isothiazol- 3-one and 2-methyl-2H- isothiazol-3-one (3:1) (C(M) IT/MIT (3:1))	-	-	Readily
2-octyl-2H-isothiazol-3-one (OIT)	-	-	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	Bioconcentration factor [BCF]	Potential
<pre>₽-octyl-2H-isothiazol-3-one (OIT)</pre>	2.45	-	low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

04.04.2022.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting : Not applicable. properties

12.7 Other adverse effects : Not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal

: Gather residues into waste containers. Liquid residue and cleaning liquids are hazardous waste and must not be emptied into drains or sewage system, but handled in accordance with national regulations. Product residues should be left at special companies which have permission for gathering this kind of wastes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 12	waste paint and varnish other than those mentioned in 08 01 11

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

Packaging

Methods of disposal : Empty packaging should be recycled or disposed of in accordance with national regulations.

Special precautions

: No additional information.

SECTION 14: Transport information

This product is not regulated for carriage according to ADR/RID, IMDG, IATA.

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name			
14.3 Transport hazard class(es)			
14.4 Packing group			
14.5 Environmental hazards	No.	N o.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in : Not available. bulk according to IMO instruments

04.04.2022. ACOUSTICS

SKIN CORROSION/IRRITATION - Category 1

SKIN CORROSION/IRRITATION - Category 2

SKIN SENSITIZATION - Category 1

SKIN SENSITIZATION - Category 1A

SKIN CORROSION/IRRITATION - Category 1C

SECTION 15: Regulatory information					
15.1 Safety, health and env EU Regulation (EC) No. 1 Other EU regulations	vironmental regulations/legislation specific for the substance or mixture 907/2006 (REACH)				
Europe inventory	· At least one component is not listed				
Persistent Organic Pollu Not listed.	: At least one component is not listed. <u>utants</u>				
VOC Directive	: This product is in scope of Directive 2004/42/CE.				
VOC max value (g/l)	: 140				
15.2 Chemical Safety Assessment	 This product contains substances for which Chemical Safety Assessments are still required. 				
SECTION 16: Other	r information				
Indicates information that	at has changed from previously issued version.				
Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number vPvB = Very Persistent and Very Bioaccumulative 				
Procedure used to derive t	the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]				
	sification Justification				
Skin Sens. 1, H317 Aquatic Chronic 3, H412	Calculation method Calculation method				
Full text of abbreviated H statements	 F301 Toxic if swallowed. H302 Harmful if swallowed. H310 Fatal in contact with skin. H311 Toxic in contact with skin. H330 Fatal if inhaled. H331 Toxic if inhaled. H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H372 Causes damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH071 Corrosive to the respiratory tract. 				
Full text of classifications [CLP/GHS]	 Acute Tox. 2 Acute Tox. 3 Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 2 Aquatic Chronic 3 Eye Dam. 1 Skin Corr. 1 				

Skin Corr. 1

Skin Irrit. 2

Skin Sens. 1 Skin Sens. 1A

Skin Corr. 1C

Date of issue/Date of revision	23.11.2022 Date of prev	ious issue 04.04.2022.	ACOUSTICS
	STOT RE 1	SPECIFIC TARGET O EXPOSURE) - Catego	RGAN TOXICITY (REPEATED ry 1
Date of issue/ Date of revision	: 11/23/2022		
Date of previous issue	: 4/4/2022		
Version	: 4		
Notice to reader			

Notice to reader

This Safety Data Sheet is prepared in accordance with Annex II (EU) No 878/2020 to Regulation (EC) No 1907/2006 (REACH). The information contained in this Safety Data Sheet is based on the present state of knowledge and current EU and national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.