Conforms to Regulation (I 2020/878 - Europe	EC) No. 1907/2006 (REACH)	, Annex II, as amended by Commission	n Regulation (EU)
Date of issue/ Date of revision	: 4/12/2023	Date of previous issue	: 11/24/2022

TIKKURILA

SAFETY DATA SHEET

ULTRA PRO PLUS 30

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name

: ULTRA PRO PLUS 30

Product description

: A waterborne acrylate paint.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Painting work

1.3 Details of the supplier of the safety data sheet

Manufacturer or DistributorTikkurila OyjP.O. Box 53FI-01301 VANTAAFINLANDTelephone +358 20 191 2000e-mail address of personresponsible for this SDSresponsible for this SDSresponsible for this SDS

1.4 Emergency telephone number

Telephone number	:	112
-		(24h)

Supplier or Manufacturer

Telephone number: Tikkurila Oyj+358 20 191 2000 (GMT +2) Mon-Fri 8-16

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

₿kin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317

Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

2.2 Label elements

Hazard pictograms



Signal word

: Warning

Date of issue/Date of revision	12.04.2023 Date of previous issue 24.11.2022. ULTRA PRO PLUS 30
Hazard statements	 F319 - Causes serious eye irritation. H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements	
General	: Not applicable.
Prevention	 P261 - Avoid breathing mist/spray. P280 - Wear protective gloves. P284 - In case of inadequate ventilation wear respiratory protection. P273 - Avoid release to the environment.
Response	 P302 + P352 - IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Storage	: Not applicable.
Disposal	: Not applicable.
Hazardous ingredients	: 4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT)
Supplemental label elements	: Contains small amounts of sensitizing substances: adipohydrazide, 1,2-benzisothiazol-3(2H)-one (BIT), reaction mass of 5-chloro-2-methyl-2H- isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1)), 3-iodo- 2-propynyl butylcarbamate (IPBC) and 2-octyl-2H-isothiazol-3-one (OIT).

Treated articles

This product contains a biocidal product for the preservation of the product during storage. Contains BIT and C(M)IT/ MIT (3:1).

2.3 Other hazards

Other hazards which do : None known. not result in classification

SECTION 3: Composition/information on ingredients

			Classification	
Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Notes
✓ methoxymethylethoxy)propanol	REACH #: 01-2119450011-60 EC: 252-104-2 CAS: 34590-94-8	≤3	Not classified.	-
3-iodo-2-propynyl butylcarbamate (IPBC)	REACH #: 01-2120762115-60 EC: 259-627-5 CAS: 55406-53-6	≤0.3	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)	-
adipohydrazide	EC: 213-999-5 CAS: 1071-93-8	≤0.3	Skin Sens. 1, H317 Aquatic Chronic 2, H411	-
4,5-dichloro-2-octyl-2H-isothiazol- 3-one (DCOIT)	EC: 264-843-8 CAS: 64359-81-5 Index: 613-335-00-8	<0.1	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071	-
1,2-benzisothiazol-3(2H)-one (BIT)	EC: 220-120-9 CAS: 2634-33-5	<0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411	-
reaction mass of 5-chloro-2-methyl- 2H-isothiazol-3-one and 2-methyl- 2H-isothiazol-3-one (3:1) (C(M)IT/	CAS: 55965-84-9 Index: 613-167-00-5	<0.0015	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330	-

Date of issue/Date of revision	12.04.2023 Date of pr	evious issue	24.11.2022.	ULTRA PRO PLUS 30	
MIT (3:1))			Eye D Skin S Aquat	Corr. 1C, H314 am. 1, H318 Sens. 1A, H317 ic Acute 1, H400 (M=100) ic Chronic 1, H410 (M=100) 71	
2-octyl-2H-isothiazol-3-one (OIT)	EC: 247-761-7 CAS: 26530-20-1 Index: 613-112-00-5	<0.001	Acute Acute Skin C Eye D Skin S Aquat	Tox. 3, H301 Tox. 3, H311 Tox. 2, H330 Corr. 1, H314 am. 1, H318 Sens. 1A, H317 ic Acute 1, H400 (M=100) ic Chronic 1, H410 (M=100) 71	
			text of t	ction 16 for the full he H statements d above.	

Notes, if applicable, refer to Notes given in Annex VI of 1272/2008/EC.

Specific concentration limits and ATE-values

Ingredient name, Specific concentration limits, ATE value

1,2-benzisothiazol-3(2H)-one (BIT) Skin Sens. 1, H317: C ≥ 0,05 %

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1)) Skin Corr. 1C, H314: C \geq 0,6 % Skin Irrit. 2, H315: 0,06 % \leq C < 0,6 % Eye Dam. 1, H318: C \geq 0,6 % Eye Irrit. 2, H319: 0,06 % \leq C < 0,6 % Skin Sens. 1A, H317: C \geq 0,0015 %

2-octyl-2H-isothiazol-3-one (OIT) Skin Sens. 1A, H317: $C \ge 0,0015 \%$ Inhalation: ATE = 0.27 mg/L (dusts/mists) Dermal: ATE = 311 mg/kg bw Oral: ATE = 125 mg/kg bw

4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT) Skin Irrit. 2, H315: 0,025 % ≤ C < 5 % Eye Irrit. 2, H319: 0,025 % ≤ C < 3 % Skin Sens. 1A, H317: C ≥ 0,0015 % Inhalation: ATE = 0.16 mg/L (dusts/mists) Oral: ATE = 567 mg/kg bw

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid me	asures
General	: In all cases of doubt, or when symptoms persist, seek medical attention. Show this safety data sheet or label to the doctor if possible.
Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with plenty of lukewarm water, keeping eyelids open. Continue to rinse for at least 15 minutes. Get medical attention if symptoms occur.
Inhalation	: Remove to fresh air. Keep person warm and at rest.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. Get medical attention if symptoms occur.
Ingestion	: If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Remove to fresh air and keep at rest in a position comfortable for breathing. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire. Recommended: Alcohol resistant foam, CO ₂ , powders or water spray/mist.
Unsuitable extinguishing media	: Do not use a direct water jet that could spread the fire.
5.2 Special hazards arising	from the substance or mixture
Hazards from the substance or mixture	: This product is not classified as flammable. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Hazardous combustion products : When exposed to high temperatures, hazardous decomposition products may be produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

5.3 Advice for firefighters

Special protective actions for fire-fighters	:	Use water spray to keep fire-exposed containers cool. This material is hazardous to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures	:	Provide adequate ventilation. Avoid breathing vapor or mist. Avoid contact with skin and eyes. See Section 8 for information on appropriate personal protective equipment.
6.2 Environmental precautions	:	Azardous to aquatic environment. Do not allow to enter drains, water courses or soil.
6.3 Methods and materials for containment and cleaning up	:	Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Preferably clean with water or detergent. Avoid using solvents.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 13 for additional waste treatment information.

12.04.2023 Date of previous issue 24.11.2022.

ULTRA PRO PLUS 30

SECTION 7: Handling and storage

7.1 Precautions for safe handling	:	Kin contact with the product and exposure to spray mist and vapor should be avoided. Avoid contact with skin and eyes. Avoid inhalation of dust from sanding. See Section 8 for information on appropriate personal protective equipment. Eating, drinking and smoking should be prohibited in areas where this material is handled and stored. Wash hands before breaks and immediately after handling the product. Avoid release to the environment.
7.2 Conditions for safe storage, including any incompatibilities	:	Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep container tightly closed. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Recommended storage temperature is +5°C+25°C. Do not allow to freeze. Store in accordance with local regulations.
7.3 Specific end use(s)	:	None.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
	EU OEL (Europe, 10/2019). Absorbed through skin. Notes: list of indicative occupational exposure limit values TWA: 50 ppm 8 hours. TWA: 308 mg/m ³ 8 hours.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn (see Personal protection). Comply with the health and safety at work laws.

Individual protection measures

Eye/face protection	: Use safety eyewear (EN166), especially during spray-application.
Hand protection	 Always wear approved protective gloves against chemicals. Gloves should be replaced regularly and if there is any sign of damage to the glove material. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Recommended glove material (EN374): > 8 hours (breakthrough time): nitrile rubber Not recommended: PVA gloves
Skin protection	: Wear suitable protective clothing.
Respiratory protection	: If ventilation during spray-application is inadequate, use respirators with combination filter AP, gas/dust filter (EN405:2001). Wear a half mask or full face respirator with gas and vapor filter A and dust filter P2 during sanding (EN140:1998, EN405:2001). During continuous and long-term work the use of motor-driven or airfed respirators is recommended (EN12941:1998). Be sure to use an approved/ certified respirator or equivalent. Check that mask fits tightly and change filter regularly.

Date of issue/Date of revision	12.04.2023 Date of previous issue	24.11.2022.	ULTRA PRO PLUS 30	
Environmental exposure controls	: For information regarding environ section 13 for waste handling, se for relevant identified uses of the	ction 7 for hand	ing and storage and section 1.2	

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance		
Physical state	:	Liquid.
Color	:	Coloured
Odor	:	Mild.
Odor threshold	:	Not relevant for the hazard assessment of the product.
рН	:	Not relevant for the hazard assessment of the product.
Melting point/freezing point	:	Not available.
Initial boiling point and	:	Not available.
boiling range		
Flash point	:	>100 °C
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not applicable. Product is a liquid.
Upper/lower flammability or explosive limits	:	Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Density	:	1.2 g/cm ³
Solubility(ies)	:	Miscible in water.
Partition coefficient: n-octanol/ water	:	Not applicable.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not relevant for the hazard assessment of the product.
Viscosity	:	Not relevant for the hazard assessment of the product.
Explosive properties	:	No explosive ingredients present.
Oxidizing properties	:	No oxidizing ingredients present.
Particle characteristics		
Median particle size	:	Not applicable.
0.0 Other information		

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	:	See Section 10.5.
10.2 Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
10.3 Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	:	Avoid extreme heat and freezing.
10.5 Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents strong acids strong alkalis

Date of issue/Date of revision	12.04.2023 Date of previous issue	24.11.2022.	ULTRA PRO PLUS 30
10.6 Hazardous decomposition products	: When exposed to high temperatu produced, such as carbon monox		

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
There is no testdata available on the product itself.
The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.
Long term exposure to spray mist may produce respiratory tract irritation. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
Acute toxicity
Not classified.
Irritation/Corrosion
Causes skin irritation. Causes serious eye irritation.
Sensitization
May cause an allergic skin reaction. The product contains sensitizing substances mentioned in sections 2 and 3.
Mutagenicity
Not classified.
Carcinogenicity
Not classified.
Reproductive toxicity
Not classified.
Teratogenicity
Not classified.
Specific target organ toxicity (single exposure)
Not classified.
Specific target organ toxicity (repeated exposure)
Not classified.
Aspiration hazard
Not classified.
11.2 Information on other hazards
11.2.1 Endocrine disrupting properties
Not applicable.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

Cological testing has not been conducted on this product. The product is classified as environmetally hazardous according to Regulation (EC) 1272/2008. Toxic to aquatic life with long lasting effects.

Do not allow to enter drains, water courses or soil.

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
ଌriodo-2-propynyl butylcarbamate (IPBC)	EC50 0.053 mg/l	Algae	72 hours
	EC50 0.16 mg/l	Daphnia	48 hours
	LC50 0.067 mg/l	Fish	96 hours
	NOEC 0.05 mg/l	Daphnia - Daphnia magna	21 days
adipohydrazide	Chronic EC50 9.19 mg/l	Algae	96 hours

Date of issue/Date of revision	12.04.2023 Date of previous issue	24.11.2022. ULTRA PRO PLUS 3	0
4,5-dichloro-2-octyl-2H- isothiazol-3-one (DCOIT)	Acute EC50 1.6 μg/l	Algae - Navicula pelliculosa	24 hours
	Acute EC50 2.1 µg/l	Crustaceans - Crassostrea virginica	48 hours
	Acute LC50 2.7 µg/l	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 0.4 µg/l	Daphnia - Daphnia magna	21 days
	Chronic NOEC 0.47 µg/l	Fish - Danio rerio	35 days
1,2-benzisothiazol-3(2H)- one (BIT)	Acute EC50 0.36 mg/l	Algae - Skeletonema costatum	72 hours
	Acute LC50 0.74 mg/l	Fish	96 hours
2-octyl-2H-isothiazol-3-one (OIT)	Acute EC50 0.00129 mg/l	Algae - Navicula pelliculosa	48 hours
	Acute EC50 0.013 mg/l	Crustaceans - Crassostrea virginica	96 hours
	Acute LC50 0.047 mg/l	Fish - Oncorhynchus mykiss	96 hours
	Chronic EC10 0.000224 mg/l	Algae - Navicula pelliculosa	48 hours
	Chronic NOEC 0.003 mg/l	Daphnia - Daphnia magna	21 days
	Chronic NOEC 0.0085 mg/l	Fish - Pimephales promelas	35 days

12.2 Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2 -octyl-2H-isothiazol-3-one (OIT)	-	-	Not readily
reaction mass of 5-chloro- 2-methyl-2H-isothiazol- 3-one and 2-methyl-2H- isothiazol-3-one (3:1) (C(M) IT/MIT (3:1))	-	-	Readily
4,5-dichloro-2-octyl-2H- isothiazol-3-one (DCOIT)	-	-	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	Bioconcentration factor [BCF]	Potential
2-octyl-2H-isothiazol-3-one (OIT)	2.45	-	low
(2-methoxymethylethoxy) propanol	0.004	-	low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting : Not applicable. properties

12.7 Other adverse effects : Not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal

: Gather residues into waste containers. Liquid residue and cleaning liquids are hazardous waste and must not be emptied into drains or sewage system, but handled in accordance with national regulations. Product residues should be left at special companies which have permission for gathering this kind of wastes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

Packaging

Methods of disposal

- : Empty packaging should be disposed of in accordance with national regulations.
- Special precautions : No additional information.

SECTION 14: Transport information

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number or ID number	<mark>₩</mark> N3082	V N3082	<mark>1</mark> /N3082
14.2 UN proper shipping name	NVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	NVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)
14.3 Transport hazard class(es)	9	9	Ø
14.4 Packing group	I II	Т	III.
14.5 Environmental hazards	<mark>∳</mark> es.	Yes.	Yes.

Additional information

ADR/RID	: $\overline{\mathbf{P}}$ his product is not regulated as a dangerous good when transported in sizes of ≤ 5 L
	or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2
	and 4.1.1.4 to 4.1.1.8.

IMDG : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IATA : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Date of issue/Date of revision	12.04.2023 Date of previous issue 24.11.2022. ULTRA PRO PLUS 30
	·
14.6 Special precautions for user	 Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do i the event of an accident or spillage.
14.7 Maritime transport in bulk according to IMO instruments	: Not available.
SECTION 15: Regula	atory information
15.1 Safety, health and envi	ronmental regulations/legislation specific for the substance or mixture
EU Regulation (EC) No. 19	07/2006 (REACH)
Other EU regulations	. At least one component is not listed
Europe inventory Persistent Organic Pollut	: At least one component is not listed.
Not listed.	
15.2 Chemical Safety Assessment	: This product contains substances for which Chemical Safety Assessments are still required.
SECTION 16: Other	information
Indicates information that	has changed from previously issued version.
Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number vPvB = Very Persistent and Very Bioaccumulative
Procedure used to derive th	ne classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]
Classi	fication Justification
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319 Skin Sens. 1, H317	Calculation method Calculation method
Aquatic Chronic 2, H411	Calculation method
Full text of abbreviated H	: H301 Toxic if swallowed.
statements	H302 Harmful if swallowed.
	H310 Fatal in contact with skin.
	H311 Toxic in contact with skin. H330 Fatal if inhaled.
	H331 Toxic if inhaled.
	H314 Causes severe skin burns and eye damage.H318 Causes serious eye damage.
	H319 Causes serious eye irritation.
	H315 Causes skin irritation. H317 May cause an allergic skin reaction.

- H317 May cause an allergic skin reaction.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- EUH071 Corrosive to the respiratory tract.

Date of issue/Date of revision	12.04.2023 Date of previous issue 24.11.2022. ULTRA PRO PLUS 30
Full text of classifications [CLP/GHS]	: Acute Tox. 2 Acute Tox. 3 Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 2 Eye Dam. 1 Eye Irrit. 2 Skin Corr. 1C Skin Sens. 1 Stor RE 1 Acute Tox. 4 ACUTE TOXICITY - Category 3 ACUTE TOXICITY - Category 4 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 2 AQUATIC HAZARD (LONG-TERM) - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SKIN CORROSION/IRRITATION - Category 1 SKIN CORROSION/IRRITATION - Category 1 SKIN SENSITIZATION - CATEGORY 1 SK
Date of issue/ Date of revision	: 4/12/2023
Date of previous issue	: 11/24/2022
Version	: 5
Notice to reader	

Notice to reader

This Safety Data Sheet is prepared in accordance with Annex II (EU) No 878/2020 to Regulation (EC) No 1907/2006 (REACH). The information contained in this Safety Data Sheet is based on the present state of knowledge and current EU and national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.