Conforms to Regulation	(EC) No. 1907/2006 (RI	EACH), Annex II, as amended by Commissic	on Regulation (EU)
2020/878 - Europe			
Date of issue/ Date of	: 1/3/2023	Date of previous issue	: 1/3/2023

revision



SAFETY DATA SHEET

FINNGARD SILICONE ALLWEATHER

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

	1.1	Pro	duc	t ide	ntifier
--	-----	-----	-----	-------	---------

: FINNGARD SILICONE ALLWEATHER **Product name**

: Facade paint

Product description

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Painting work

1.3 Details of the supplier of the safety data sheet

Manufacturer or Distributor Tikkurila Ovi P.O. Box 53 FI-01301 VANTAA FINLAND Telephone +358 20 191 2000 e-mail address of person : Tikkurila Oyj, responsible for this SDS Product Safety, e-mail: productsafety@tikkurila.com

1.4 Emergency telephone number

Telephone number	:	112
-		(24h)

Supplier or Manufacturer

: Tikkurila Oyj **Telephone number** +358 20 191 2000 (GMT +2) Mon-Fri 8-16

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Skin Sens. 1, H317 Aquatic Chronic 3, H412 The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

2.2 Label elements

Hazard pictograms



Signal word	:	Warning
Hazard statements	:	H317 - May cause an allergic skin reaction. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements		
General	:	Not applicable.

Date of issue/Date of revision	03.01.2023 Date of previous issue	03.01.2023.	FINNGARD SILICONE ALLWEATHER
Prevention	 P261 - Avoid breathing mist/spray. P280 - Wear protective gloves. P284 - In case of inadequate ventil P273 - Avoid release to the environ 		iratory protection.
Response	: P302 + P352 - IF ON SKIN: Wash	with plenty of s	oap and water.
Storage	: Not applicable.		
Disposal	: Not applicable.		
Hazardous ingredients	: 4,5-dichloro-2-octyl-2H-isothiazol-3	-one (DCOIT)	
Supplemental label elements	: Contains small amounts of sensitiz (BIT), reaction mass of 5-chloro-2- isothiazol-3-one (3:1) (C(M)IT/MIT	-methyl-2H-isot	

Treated articles

This product contains a biocidal product for the preservation of the product during storage. Contains BIT, C(M)IT/MIT (3:1).

2.3 Other hazards

Other hazards which do : None known. not result in classification

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture			
Product/ingredient name	Identifiers	%	<u>Classification</u> Regulation (EC) No. 1272/2008 [CLP]	Notes
3-iodo-2-propynyl butylcarbamate (IPBC)	REACH #: 01-2120762115-60 EC: 259-627-5 CAS: 55406-53-6	<0.1	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)	-
1,2-benzisothiazol-3(2H)-one (BIT)	EC: 220-120-9 CAS: 2634-33-5	<0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411	-
4,5-dichloro-2-octyl-2H-isothiazol- 3-one (DCOIT)	EC: 264-843-8 CAS: 64359-81-5 Index: 613-335-00-8	<0.025	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071	-
bronopol	REACH #: 01-2119980938-15 EC: 200-143-0 CAS: 52-51-7 Index: 603-085-00-8	≤0.1	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 (M=10)	-
reaction mass of 5-chloro-2-methyl- 2H-isothiazol-3-one and 2-methyl- 2H-isothiazol-3-one (3:1) (C(M)IT/ MIT (3:1))	CAS: 55965-84-9 Index: 613-167-00-5	<0.001	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071 See Section 16 for the full text of the H statements declared above.	-

03.01.2023 Date of previous issue

03.01.2023.

Notes, if applicable, refer to Notes given in Annex VI of 1272/2008/EC.

Specific concentration limits and ATE-values

Ingredient name, Specific concentration limits, ATE value

1,2-benzisothiazol-3(2H)-one (BIT) Skin Sens. 1, H317: C \ge 0,05 %

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1)) Skin Corr. 1C, H314: $C \ge 0,6 \%$ Skin Irrit. 2, H315: $0,06 \% \le C < 0,6 \%$ Eye Dam. 1, H318: $C \ge 0,6 \%$ Eye Irrit. 2, H319: $0,06 \% \le C < 0,6 \%$ Skin Sens. 1A, H317: $C \ge 0,0015 \%$ 4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT) Skin Irrit. 2, H315: $0,025 \% \le C < 5 \%$

Skin Irrit. 2, H315: $0,025 \% \le C < 5 \%$ Eye Irrit. 2, H319: $0,025 \% \le C < 3 \%$ Skin Sens. 1A, H317: $C \ge 0,0015 \%$ Inhalation: ATE = 0.16 mg/L (dusts/mists) Oral: ATE = 567 mg/kg bw

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

General	: In all cases of doubt, or when symptoms persist, seek medical attention. Show this safety data sheet or label to the doctor if possible.
Eye contact	 Check for and remove any contact lenses. Immediately flush eyes with plenty of lukewarm water, keeping eyelids open. Continue to rinse for at least 15 minutes. Get medical attention if symptoms occur.
Inhalation	: Remove to fresh air. Keep person warm and at rest.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. Get medical attention if symptoms occur.
Ingestion	: If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Remove to fresh air and keep at rest in a position comfortable for breathing. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire. Recommended: Alcohol resistant foam, CO ₂ , powders or water spray/mist.
Unsuitable extinguishing media	: Do not use a direct water jet that could spread the fire.

5.2 Special hazards arising from the substance or mixture

Date of issue/Date of revision		03.01.2023 Date of previous issue	03.01.2023.	FINNGARD SILICONE ALLWEATHER
Hazards from the substance or mixture	:	This product is not classified as f Exposure to decomposition product		
Hazardous combustion products	:	When exposed to high temperature produced, such as carbon monop		
5.3 Advice for firefighters				
Special protective actions for fire-fighters	:	Use water spray to keep fire-expandence aquatic organisms. Fire water co and prevented from being discha	ontaminated with	
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate breathing apparatus (SCBA) with mode.		

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures	:	Provide adequate ventilation. Avoid breathing vapor or mist. Avoid direct skin contact with product. See Section 8 for information on appropriate personal protective equipment.
6.2 Environmental precautions	:	Hazardous to aquatic environment. Do not allow to enter drains, water courses or soil.
6.3 Methods and materials for containment and cleaning up	:	Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Preferably clean with water or detergent. Avoid using solvents.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling	:	Skin contact with the product and exposure to spray mist and vapor should be avoided. Avoid contact with skin and eyes. Avoid inhalation of dust from sanding. See Section 8 for information on appropriate personal protective equipment. Eating, drinking and smoking should be prohibited in areas where this material is handled and stored. Wash hands before breaks and immediately after handling the product. Avoid release to the environment.
7.2 Conditions for safe storage, including any incompatibilities	:	Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep container tightly closed. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Recommended storage temperature is +5°C+25°C. Do not allow to freeze. Store in accordance with local regulations.
7.3 Specific end use(s)	:	None.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits No exposure limit value known.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

DNELs/DMELs

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn (see Personal protection). Comply with the health and safety at work laws.

03.01.2023.

Individual protection measures

Eye/face protection	Use safety eyewear (EN166), especially during spray-application.		
Hand protection	 Always wear approved protective gloves against chemicals. Gloves should be replaced regularly and if there is any sign of damage to the glove material. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Recommended glove material (EN374): > 8 hours (breakthrough time): nitrile rubber Not recommended: PVA gloves 		
Skin protection	: Wear suitable protective clothing.		
Respiratory protection	: If ventilation during spray-application is inadequate, use respirators with combination filter AP, gas/dust filter (EN405:2001). Wear a half mask or full face respirator with gas and vapor filter A and dust filter P2 during sanding (EN140:1998, EN405:2001). During continuous and long-term work the use of motor-driven or air-fed respirators is recommended (EN12941:1998). Be sure to use an approved/ certified respirator or equivalent. Check that mask fits tightly and change filter regularly.		
Environmental exposure controls	: For information regarding environmental protection measures, please refer to section 13 for waste handling, section 7 for handling and storage and section 1.2 for relevant identified uses of the substance or mixture and uses advised against.		

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

5.1 mornation on basic physica	u	na chemical properties
Appearance		
Physical state	:	Liquid.
Color	:	Various
Odor	:	Mild.
Odor threshold	:	Not relevant for the hazard assessment of the product.
рН	:	7 to 9
Melting point/freezing point	:	0°C (water)
Initial boiling point and	:	100°C (water)
boiling range		
Flash point	;	>100°C
Evaporation rate		Not relevant due to the nature of the product.
Flammability (solid, gas)	:	Not applicable. Product is a liquid.
Upper/lower flammability or explosive limits	:	No flammable ingredients present.
Vapor pressure	:	3.2 kPa [room temperature] (water)
Vapor density	:	Not relevant for the hazard assessment of the product.
Density	:	1.2 to 1.5 g/cm ³
Solubility(ies)	:	Miscible in water.
Partition coefficient: n-octanol/ water	:	Not applicable.
Auto-ignition temperature	:	Not relevant due to the nature of the product.
Decomposition temperature	:	Not relevant for the hazard assessment of the product.
Viscosity	:	Not relevant for the hazard assessment of the product.
Explosive properties	:	No explosive ingredients present.
Oxidizing properties	:	No oxidizing ingredients present.

03.01.2023 Date of previous issue

03.01.2023.

FINNGARD SILICONE ALLWEATHER

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

No additional information. SECTION 10: Stability and reactivity : See Section 10.5. 10.1 Reactivity : Stable under recommended storage and handling conditions (see Section 7). 10.2 Chemical stability 10.3 Possibility of : Under normal conditions of storage and use, hazardous reactions will not occur. hazardous reactions 10.4 Conditions to avoid : Avoid extreme heat and freezing. **10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents strong acids strong alkalis 10.6 Hazardous When exposed to high temperatures, hazardous decomposition products may be decomposition products produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There is no testdata available on the product itself.

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Long term exposure to spray mist may produce respiratory tract irritation. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Acute toxicity

Not classified.

Irritation/Corrosion

Not classified.

Sensitization

May cause an allergic skin reaction.

The product contains sensitizing substances mentioned in sections 2 and 3.

Mutagenicity

Not classified.

Carcinogenicity

Not classified.

Reproductive toxicity

Not classified.

Teratogenicity

Not classified.

Specific target organ toxicity (single exposure)

Not classified.

Specific target organ toxicity (repeated exposure)

Not classified.

Aspiration hazard

Not classified.

11.2 Information on other hazards

03.01.2023 Date of previous issue

03.01.2023.

11.2.1 Endocrine disrupting properties

Not applicable.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

Ecological testing has not been conducted on this product. The product is classified as environmetally hazardous according to Regulation (EC) 1272/2008. Harmful to aquatic life with long lasting effects.

Do not allow to enter drains, water courses or soil.

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
3-iodo-2-propynyl butylcarbamate (IPBC)	EC50 0.053 mg/l	Algae	72 hours
	EC50 0.16 mg/l	Daphnia	48 hours
	LC50 0.067 mg/l	Fish	96 hours
	NOEC 0.05 mg/l	Daphnia - Daphnia magna	21 days
1,2-benzisothiazol-3(2H)- one (BIT)	Acute EC50 0.36 mg/l	Algae - Skeletonema costatum	72 hours
	Acute LC50 0.74 mg/l	Fish	96 hours
4,5-dichloro-2-octyl-2H- isothiazol-3-one (DCOIT)	Acute EC50 1.6 µg/l	Algae - Navicula pelliculosa	24 hours
	Acute EC50 2.1 μg/l	Crustaceans - Crassostrea virginica	48 hours
	Acute LC50 2.7 µg/l	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 0.4 µg/l	Daphnia - Daphnia magna	21 days
	Chronic NOEC 0.47 µg/l	Fish - Danio rerio	35 days
bronopol	Acute EC50 0.068 mg/l	Algae - Anabaena flos aqua	72 hours

12.2 Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
reaction mass of 5-chloro- 2-methyl-2H-isothiazol- 3-one and 2-methyl-2H- isothiazol-3-one (3:1) (C(M) IT/MIT (3:1))	-	-	Readily
4,5-dichloro-2-octyl-2H- isothiazol-3-one (DCOIT)	-	-	Not readily

12.3 Bioaccumulative

potential

Product/ingredient name	LogPow	Bioconcentration factor [BCF]	Potential
bronopol	0.18	-	low

Date of issue/Date of revision	03.01.2023 Date of previous issue	03.01.2023.	FINNGARD SILICONE ALLWEATHER
12.4 Mobility in soil			
Soil/water partition coefficient (Koc)	: Not available.		
Mobility	: Not available.		

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting : Not applicable. properties

12.7 Other adverse effects : Not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal

: Gather residues into waste containers. Liquid residue and cleaning liquids are hazardous waste and must not be emptied into drains or sewage system, but handled in accordance with national regulations. Product residues should be left at special companies which have permission for gathering this kind of wastes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 12	waste paint and varnish other than those mentioned in 08 01 11

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

Packaging

- **Methods of disposal** : Empty packaging should be recycled or disposed of in accordance with national regulations.
- Special precautions : No additional information.

SECTION 14: Transport information

This product is not regulated for carriage according to ADR/RID, IMDG, IATA.

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.

Additional information

ΙΑΤΑ

: The environmentally hazardous substance mark may appear if required by other transportation regulations.

Date of issue/Date of revision		03.01.2	023 Date of previous issue	03.01.2023.	FINNGARD SILICONE ALLWEATHER
14.6 Special precautions for user	:	upright		persons transpor	sport in closed containers that are rting the product know what to do in
14.7 Maritime transport in bulk according to IMO instruments	:	Not ava	ailable.		
SECTION 15: Regula	ato	ry inf	ormation		
15.1 Safety, health and envir	ron	mental r	egulations/legislation s	pecific for the s	substance or mixture
EU Regulation (EC) No. 190 Other EU regulations)7/2	006 (RE	ACH)		
Europe inventory	:	Not det	termined.		
Persistent Organic Polluta Not listed.	ants	2			
VOC Directive	:	This pr	oduct is in scope of Dired	tive 2004/42/CE.	
VOC max value (g/l)		40	·		
15.2 Chemical Safety Assessment	:	This pr require		es for which Cher	mical Safety Assessments are still
SECTION 16: Other i	inf	ormat	tion		
Indicates information that I	has	change	d from previously issued	version.	
Abbreviations and acronyms	:	CLP = 1272/2 DMEL DNEL : EUH st PBT = PNEC RRN =		Level I Hazard statemen ive and Toxic ncentration mber	
Procedure used to derive the	e cl	assifica	tion according to Regu	lation (EC) No. 7	1272/2008 [CLP/GHS]
Classif	ficat	tion			Justification
Skin Sens. 1, H317 Aquatic Chronic 3, H412				lation method lation method	
Full text of abbreviated H	:	H301 H302	Toxic if swallowed. Harmful if swallowed		

	1 11001	revite in official official
statements	H302	Harmful if swallowed.
	H310	Fatal in contact with skin.
	H312	Harmful in contact with skin.
	H330	Fatal if inhaled.

- H330 Fatal if inhaled. H331 Toxic if inhaled.
- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H335 May cause respiratory irritation.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH071 Corrosive to the respiratory tract.

Date of issue/Date of revision	03.01.2023 Date of previous	issue 03.01.2023.	FINNGARD SILICONE ALLWEATHER
Full text of classifications	: Acute Tox. 2	ACUTE TOXICITY - Cate	egory 2
[CLP/GHS]	Acute Tox. 3	ACUTE TOXICITY - Cate	egory 3
	Acute Tox. 4	ACUTE TOXICITY - Cate	egory 4
	Aquatic Acute 1	AQUATIC HAZARD (AC	UTE) - Category 1
	Aquatic Chronic 1	AQUATIC HAZARD (LO	NG-TERM) - Category 1
	Aquatic Chronic 2	AQUATIC HAZARD (LO	NG-TERM) - Category 2
	Aquatic Chronic 3	AQUATIC HAZARD (LO	
	Eye Dam. 1		E/ EYE IRRITATION - Category 1
	Skin Corr. 1	SKIN CORROSION/IRR	
	Skin Corr. 1C	SKIN CORROSION/IRR	
	Skin Irrit. 2	SKIN CORROSION/IRR	
	Skin Sens. 1	SKIN SENSITIZATION -	
	Skin Sens. 1A	SKIN SENSITIZATION -	
	STOT RE 1	SPECIFIC TARGET OR EXPOSURE) - Category	GAN TOXICITY (REPEATED 1
	STOT SE 3		GAN TOXICITY (SINGLE
Date of issue/ Date of revision	: 1/3/2023		•
Date of previous issue	: 1/3/2023		
Version	: 4		
Notice to reader			

Notice to reader

This Safety Data Sheet is prepared in accordance with Annex II (EU) No 878/2020 to Regulation (EC) No 1907/2006 (REACH). The information contained in this Safety Data Sheet is based on the present state of knowledge and current EU and national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.