2020/878 - Europe

Date of issue/ Date of : 11/2/2022 Date of previous issue : 7/9/2021 revision



SAFETY DATA SHEET

FONTECRYL SC-MR 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : FONTECRYL SC-MR 10
Product description : A waterborne acrylate paint.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Painting work

1.3 Details of the supplier of the safety data sheet

Manufacturer or Distributor

Tikkurila Oyj P.O. Box 53 FI-01301 VANTAA FINLAND

Telephone +358 20 191 2000

a mail address of paragr

e-mail address of person : Tikkurila Oyj, responsible for this SDS : Product Safety,

e-mail: productsafety@tikkurila.com

1.4 Emergency telephone number

Telephone number : 112

(24h)

Supplier or Manufacturer

Telephone number : Tikkurila Oyj

+358 20 191 2000 (GMT +2) Mon-Fri 8-16

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

2.2 Label elements

Signal word : No signal word.

Hazard statements : H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

General : Not applicable.

Prevention: P273 - Avoid release to the environment.

Response : Not applicable.

Storage : Not applicable.

Disposal : Not applicable.

Version : 4 1/10

Supplemental label elements

: Contains 2,4,7,9-tetramethyldec-5-yne-4,7-diol, 1,2-benzisothiazol-3(2H)-one (BIT) and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1)). May produce an allergic reaction.

Wear protective gloves.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Treated articles

This product contains a biocidal product for the preservation of the product during storage. Contains C(M)IT/MIT (3:1) and BIT.

2.3 Other hazards

Other hazards which do not result in classification

: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

			<u>Classification</u>	
Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Notes
2 -butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	<10	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	-
trizinc bis(orthophosphate)	REACH #: 01-2119485044-40 EC: 231-944-3 CAS: 7779-90-0 Index: 030-011-00-6	≤2.1	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	-
zinc oxide	REACH #: 01-2119463881-32 EC: 215-222-5 CAS: 1314-13-2 Index: 030-013-00-7	≤0.39	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	-
2,4,7,9-tetramethyldec-5-yne-4,7-dio	REACH #: 01-2119954390-39 EC: 204-809-1 CAS: 126-86-3	≤0.3	Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 3, H412	-
ammonia	REACH #: 01-2119488876-14 EC: 215-647-6 CAS: 1336-21-6 Index: 007-001-01-2	≤0.3	Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 (M=1)	В
1,2-benzisothiazol-3(2H)-one (BIT)	EC: 220-120-9 CAS: 2634-33-5	<0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411	-
reaction mass of 5-chloro-2-methyl- 2H-isothiazol-3-one and 2-methyl- 2H-isothiazol-3-one (3:1) (C(M)IT/ MIT (3:1))	CAS: 55965-84-9 Index: 613-167-00-5	<0.001	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071 See Section 16 for the full text of the H statements	-

Notes, if applicable, refer to Notes given in Annex VI of 1272/2008/EC.

Specific concentration limits and ATE-values

Version : 4 2/10

Ingredient name, Specific concentration limits, ATE value

ammonia

STOT SE 3, H335: C ≥ 5 %

2-butoxyethanol

Inhalation: ATE = 3 mg/L (Vapours)
Oral: ATE = 1200 mg/kg bw

1,2-benzisothiazol-3(2H)-one (BIT) Skin Sens. 1, H317: C ≥ 0,05 %

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1))

Skin Corr. 1C, H314: $C \ge 0.6$ % Skin Irrit. 2, H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1, H318: $C \ge 0.6$ % Eye Irrit. 2, H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A, H317: $C \ge 0.0015$ %

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

General : In all cases of doubt, or when symptoms persist, seek medical attention. Show this

safety data sheet or label to the doctor if possible.

Eye contact: Check for and remove any contact lenses. Immediately flush eyes with plenty of

lukewarm water, keeping eyelids open. Continue to rinse for at least 15 minutes.

Inhalation: Remove to fresh air.

Skin contact: Wash skin thoroughly with soap and water or use recognized skin cleanser. Do

NOT use solvents or thinners.

Ingestion : If accidentally swallowed rinse the mouth with plenty of water (only if the person is

conscious). If significant amounts have been swallowed or if symptoms persist,

seek medical attention.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

: Use an extinguishing agent suitable for the surrounding fire. Recommended: Alcohol resistant foam, CO₂, powders or water spray/mist.

Alcohol resistant rount, CO₂, powders or water spraymins

Unsuitable extinguishing media

: Do not use a direct water jet that could spread the fire.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: This product is not classified as flammable. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Hazardous combustion products

: When exposed to high temperatures, hazardous decomposition products may be produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

Version : 4 3/10

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Use water spray to keep fire-exposed containers cool. This material is hazardous to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

: Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

: Hazardous to aquatic environment. Do not allow to enter drains, water courses or

6.3 Methods and materials for containment and cleaning up

: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Preferably clean with water or detergent. Avoid using solvents.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Skin contact with the product and exposure to spray mist and vapor should be avoided. Avoid contact with skin and eyes. Avoid inhalation of dust from sanding. See Section 8 for information on appropriate personal protective equipment. Eating, drinking and smoking should be prohibited in areas where this material is handled and stored. Wash hands before breaks and immediately after handling the product. Avoid release to the environment.

7.2 Conditions for safe storage, including any incompatibilities

: Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep container tightly closed. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Recommended storage temperature is +5°C ...+25°C. Do not allow to freeze. Store in accordance with local regulations.

7.3 Specific end use(s) : None.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
	EU OEL (Europe, 10/2019). Absorbed through skin. Notes: list of indicative occupational exposure limit values TWA: 20 ppm 8 hours. TWA: 98 mg/m³ 8 hours. STEL: 50 ppm 15 minutes. STEL: 246 mg/m³ 15 minutes.

procedures

Recommended monitoring: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

Version: 4

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Comply with the health and safety at work laws.

Individual protection measures

Eye/face protection Safety eyewear should be used when there is a likelihood of exposure. Use safety

eyewear (EN166), especially during spray-application.

Hand protection : Wear protective gloves. Gloves should be replaced regularly and if there is any

> sign of damage to the glove material. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be

followed.

Recommended glove material (EN374): > 8 hours (breakthrough time): nitrile rubber

Not recommended: PVA gloves

Skin protection : Wear appropriate personal protective clothing to prevent skin contact.

Respiratory protection If ventilation during spray-application is inadequate, use respirators with

> combination filter AP, gas/dust filter (EN405:2001). Wear a respirator with type P2 filter during sanding (EN149:2001). Be sure to use an approved/certified respirator

or equivalent. Check that mask fits tightly and change filter regularly.

Environmental exposure

controls

: For information regarding environmental protection measures, please refer to section 13 for waste handling, section 7 for handling and storage and section 1.2

for relevant identified uses of the substance or mixture and uses advised against. SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid. Color : Coloured Odor : Mild.

Odor threshold : Not relevant for the hazard assessment of the product. pН Not relevant for the hazard assessment of the product.

Melting point/freezing point Initial boiling point and

boiling range

: Not available. : Not available.

: >100°C Flash point

: Not available. **Evaporation rate**

Flammability (solid, gas) : Not applicable. Product is a liquid.

Upper/lower flammability or

explosive limits

: Not available.

: Not available. Vapor pressure Vapor density : Not available. Density : 1.2 to 1.3 g/cm³ Miscible in water. Solubility(ies) Partition coefficient: n-octanol/ : Not applicable.

water

Auto-ignition temperature : Not available.

Decomposition temperature : Not relevant for the hazard assessment of the product.

: Not relevant for the hazard assessment of the product. **Viscosity**

Explosive properties : No explosive ingredients present. Oxidizing properties : No oxidizing ingredients present.

Particle characteristics

Median particle size : Not applicable.

Version : 4

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity : See Section 10.5.

10.2 Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : Avoid extreme heat and freezing.

10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents strong acids strong alkalis

10.6 Hazardous decomposition products

: When exposed to high temperatures, hazardous decomposition products may be produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There is no testdata available on the product itself.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Long term exposure to spray mist may produce respiratory tract irritation. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Acute toxicity

Not classified.

Irritation/Corrosion

Not classified.

Sensitization

Not classified.

The product contains sensitizing substances mentioned in sections 2 and 3.

Mutagenicity

Not classified.

Carcinogenicity

Not classified.

Reproductive toxicity

Not classified.

Teratogenicity

Not classified.

Specific target organ toxicity (single exposure)

Not classified.

Specific target organ toxicity (repeated exposure)

Not classified.

Aspiration hazard

Not classified.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not applicable.

11.2.2 Other information

Version : 4 6/10

Not available.

SECTION 12: Ecological information

Ecological testing has not been conducted on this product.

The product is classified as environmetally hazardous according to Regulation (EC) 1272/2008. Harmful to aquatic life with long lasting effects.

Do not allow to enter drains, water courses or soil.

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
trizinc bis(orthophosphate)	Acute EC50 0.8 mg/l	Algae	72 hours
zinc oxide	Acute EC50 0.17 mg/l	Algae - Selenastrum capricornutum	72 hours
	Acute EC50 0.481 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 2.525 mg/l Fresh water	Fish - Danio rerio - Adult	96 hours
2,4,7,9-tetramethyldec- 5-yne-4,7-diol	EC50 82 mg/l	Algae - Selenastrum capricornutum	72 hours
	EC50 15 mg/l	Aquatic plants	3 days
	EC50 91 mg/l	Daphnia	2 days
	EC50 91 mg/l	Daphnia	48 hours
	LC50 36 mg/l	Fish	4 days
	NOEC 43 mg/l	Daphnia	2 days
	NOEC 32 mg/l	Fish	4 days
ammonia	LC50 0.53 mg/l	Fish	96 hours
1,2-benzisothiazol-3(2H)- one (BIT)	Acute EC50 0.36 mg/l	Algae - Skeletonema costatum	72 hours
	Acute LC50 0.74 mg/l	Fish	96 hours

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
2 -butoxyethanol	-	90.4 % - Readily - 28 days	-	-
2,4,7,9-tetramethyldec- 5-yne-4,7-diol	-	15.7 % - Not readily - 57 days	-	-
Product/ingredient name	Aquatic half-life	Photolysis		Biodegradability
reaction mass of 5-chloro- 2-methyl-2H-isothiazol- 3-one and 2-methyl-2H- isothiazol-3-one (3:1) (C(M) IT/MIT (3:1))	-	-		Readily
2-butoxyethanol	_	_		Readily

12.3 Bioaccumulative potential

Version : 4 7/10

Product/ingredient name	LogP _{ow}	Bioconcentration factor [BCF]	Potential
z ínc oxide	-	28960	high
trizinc bis(orthophosphate)	-	60960	high
2-butoxyethanol	0.81	<100	low

02.11.2022 Date of previous issue

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

Date of issue/Date of revision

: Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting

properties

: Not applicable.

12.7 Other adverse effects : Not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal

: Gather residues into waste containers. Liquid residue and cleaning liquids are hazardous waste and must not be emptied into drains or sewage system, but handled in accordance with national regulations. Product residues should be left at special companies which have permission for gathering this kind of wastes.

09.07.2021.

FONTECRYL SC-MR 10

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11* 08 01 12	waste paint and varnish containing organic solvents or other hazardous substances waste paint and varnish other than those mentioned in 08 01 11

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

Packaging

Methods of disposal

: Empty packaging should be recycled or disposed of in accordance with national

regulations.

Special precautions

: No additional information.

SECTION 14: Transport information

This product is not regulated for carriage according to ADR/RID, IMDG, IATA.

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-

Version : 4 8/10

Date of issue/Date of revision	02.11.2022 Date of previous	ISSUE 09.07.2021.	FONTECRYL SC-MR 10	
14.5 Environmental hazards	No.	No.	No.	

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO

instruments

: Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Other EU regulations

Europe inventory : At least one component is not listed.

Persistent Organic Pollutants

Not listed.

VOC Directive : This product is in scope of Directive 2004/42/CE.

15.2 Chemical Safety

Assessment

: This product contains substances for which Chemical Safety Assessments are still

required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and

acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification **Justification**

Aquatic Chronic 3, H412 Calculation method

Full text of abbreviated H statements

: H301 Toxic if swallowed. H302 Harmful if swallowed.

Fatal in contact with skin. H310

Fatal if inhaled. H330 H331 Toxic if inhaled.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage. Causes serious eye irritation. H319

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects. H411 Harmful to aquatic life with long lasting effects. H412

EUH071 Corrosive to the respiratory tract.

Version : 4 9/10

Date of issue/Date of revision	02.11.2022 Date of previo	us issue 09.07.2021.	FONTECRYL SC-MR 10
Full text of classifications [CLP/GHS]	: Acute Tox. 2 Acute Tox. 3 Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 2 Aquatic Chronic 3 Eye Dam. 1 Eye Irrit. 2 Skin Corr. 1B Skin Corr. 1C Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1 Skin Sens. 1 Skin Sens. 1B STOT SE 3	ACUTE TOXICITY - CONTROLL ACUTE TOXICITY - CONTROLL ACUTE TOXICITY - CONTROLL ACUATIC HAZARD (LONG ACUATIC) EVEN EYE DAMA SERIOUS EYE DAMA SKIN CORROSION/IF SKIN CORROSION/IF SKIN CORROSION/IF SKIN SENSITIZATION SKIN SENSITIZATION SKIN SENSITIZATION SKIN SENSITIZATION	rategory 2 rategory 3 rategory 4 ACUTE) - Category 1 LONG-TERM) - Category 1 LONG-TERM) - Category 2 LONG-TERM) - Category 3 LGE/ EYE IRRITATION - Category 1 LGE/ EYE IRRITATION - Category 2 RRITATION - Category 1B RRITATION - Category 1C RRITATION - Category 2 N - Category 1 N - Category 1 N - Category 1 N - Category 1B DRGAN TOXICITY (SINGLE
Date of issue/ Date of revision	: 11/2/2022	EM GGGNE) - Galege	, 0

: 7/9/2021 Date of previous issue

Version : 4

Notice to reader

This Safety Data Sheet is prepared in accordance with Annex II (EU) No 878/2020 to Regulation (EC) No 1907/2006 (REACH). The information contained in this Safety Data Sheet is based on the present state of knowledge and current EU and national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Version: 4 10/10